

SOLIDFLOOR ECO

Solidfloor Eco Comfort Click Rye

2015905

152 x 22,8 cm
5,2/0,55 mm



Packaging

Boards per pack:	8 boards
m ² per pack:	2,77 m ²
Weight per pack:	18,815 kg
Number of packs on a pallet:	36

Dimensions

Length:	152 cm
Width:	22,8 cm
Thickness:	Total: 5,2 mm, including integrated sub floor Top layer: 0.3 mm

Use

Usage class:	23 intensive domestic residential use 33 intensive commercial use
Floor heating (EN12524):	Yes, up to 29C° only suitable for installation over Hydronic Radiant heating systems
Suitable for office chairs?:	Yes
Resistant to chemicals? (EN 423):	Yes, test result = 0. (Gra-matt coating)
Acoustic reduction of impact sound:	Delat Lw: 17dB

Specifications

Lightfastness (ISO 105-B02):	≥6
Wear resistance (EN13329:2006+A1:2008Annex E):	6000 cycles
Thermal conductivity:	0.114 W/(m·K)
Thermal resistance:	0.046 (m ² ·K)/W
Residual indentation (ISO 24343-1):	<0,13 mm
Dimensional stability:	X direction: 0.00% Y direction: 0.00%
Repetition factor:	4
Locking system:	Uni-Push
Bevel:	4-sided, micro bevel
Fire class:	Cfl-S1
VOC Emission:	A+

Instructions and Maintenance

Maintain with Solidfloor™ Easy Protect & Solidfloor™ Easy Clean (visit www.solidfloor.com for more information).

All indicated values are guide values; production-dependent deviations cannot be avoided.