

# MINERAL DRYBACK

Mineral Dryback Amber Rustic Grade

2016000

190 x 19 cm  
7/1 mm



## Packaging

|                              |                      |
|------------------------------|----------------------|
| Boards per pack:             | 6 boards             |
| m <sup>2</sup> per pack:     | 2,166 m <sup>2</sup> |
| Weight per pack:             | 28,2 kg              |
| Number of packs on a pallet: | 30                   |

## Dimensions

|            |   |
|------------|---|
| Length:    | 190 cm  |
| Width:     | 19 cm   |
| Thickness: | Total: 7 mm, including<br>integrated sub floor<br>Oak veneer Top layer: 1mm<br>SPC Mineral Core carrier: 5 mm<br>Integrated Cork subfloor: 1 mm |

## Use

|                          |                 |
|--------------------------|-----------------|
| Floor heating (EN12524): | Yes, up to 27C° |
|--------------------------|-----------------|

Integrated Cork subfloor - This allows the floor to be installed directly as a floating floor on the screed without the need for an additional underlay.

## Specifications

|                        |                      |
|------------------------|----------------------|
| Formaldehyde emission: | E1                   |
| Insulation value:      | R=0,07m2 k/w         |
| Brinell hardness:      | Average HB 3.7       |
| Locking system:        | 5G                   |
| Bevel:                 | 4-sided, micro bevel |
| Fire class:            | Bfl-S1               |
| VOC Emission:          | A+                   |

## Instructions and Maintenance

Does not need to be oiled after installation.  
Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit [www.solidfloor.com](http://www.solidfloor.com) for more information).

All indicated values are guide values;  
production-dependent deviations cannot be avoided.